

## Hex Brass Jam Nuts

### Hex Brass Jam Nuts



Brass Hex Jam Nuts ANSI  
/ ASME B18.2.2 Jam Nuts

### Brass hex Jam Nuts ANSI/ASME B18.2.2. Brass Jam Nuts

Thread Size	Hex Size Across Flats			Size Across Corners		Nut Thickness			
	Basic	Max	Min	Max	Min	Basic	Max	Min	
1/4 "	.250	7/16	.438	.428	.502	.488	5/32	.163	.150
5/16 "	.312	1/2	.500	.489	.577	.557	3/16	.195	.180
3/8 "	.375	9/16	.562	.551	.650	.628	7/32	.227	.210
7/16 "	.437	11/16	.688	.675	.794	.768	1/4	.260	.240
1/2 "	.500	3/4	.750	.736	.866	.840	5/16	.323	.302
9/16 "	.562	7/8	.875	.851	1.010	.982	5/16	.324	.301
5/8 "	.625	15/16	.938	.922	1.093	1.051	3/8	.387	.363
3/4 "	.750	1-1/8	1.125	1.088	1.299	1.240	27/64	.446	.398
7/8 "	.875	1-5/16	1.312	1.269	1.516	1.447	31/64	.510	.458
1 "	1.000	1-1/2	1.500	1.450	1.732	1.653	35/64	.575	.519
1-1/8 "	1.125	1-11/16	1.688	1.631	1.949	1.859	39/64	.639	.579
1-1/4 "	1.250	1-7/8	1.875	1.812	2.165	2.066	23/32	.751	.687
1-3/8 "	1.375	2-1/16	2.062	1.994	2.382	2.273	25/32	.815	.747
1-1/2 "	1.500	2-1/4	2.250	2.175	2.598	2.480	27/32	.880	.808
1-3/4 "	1.750	2-5/8	2.625	2.538	3.031	2.893	31/32	1.009	.929
2 "	2.000	3	3.000	2.900	3.464	3.306	1-3/32	1.138	1.050

We are one of the leading suppliers of Brass Jam Nuts Hex jam nuts thin Jam nuts to ANSI standards.

**Description:** A Jam nuts is a six sided Brass nut with double sided chamfers used in fastening of bolts screws and fasteneing products

**Threads:** UNC UNEF UNF UNS and also metric BSW BSPP BSPT NPT

**Jam nuts** are thin hex nuts usually used as a second nut that is "jammed" (tightened) against a full size nut or alone as a thin nut. They are used to "lock" turnbuckles and control linkages, like steering tie rods, after adjustment. Hex is short for hexagon, which means they have six sides. Jam nuts are also known as: Jam nuts are used without lock washers when jammed against another nut, and may be used with lock washers when installed as a single nut.

When used as a "jam" fitting, the jam nut is installed first and contacts the mating surface. The full size nut is installed second and contacts the jam nut.

---

**ADDEESS:**

**Conex Brass Screws Fasteners**

Plot 10 B GIDC IND Estate Jamnagar 361004 INDIA

**CONTACTS:**

PHONE : 91-22-43449300 / 43449327

FAX : 91-22-22834046 / 40023682

EMAIL : [sales@conexscrews.com](mailto:sales@conexscrews.com)

[CONTACT US](#) | [BACK TO HOME PAGE](#)

**KEYWORDS:**

**Brass jam nuts, Jamming Nuts Brass, hex jam nuts, ANSI B18.2.2 Jam nuts, Hexagonal Thin jam nuts, Brass jam lock nuts, Jam nuts manufacturers india, Jam nuts exporters suppliers india,**