

DIN 439 Brass hex thin jam nuts

DIN 439 Brass Hex Thin Jam Nuts



DIN 439 Brass Hex Thin Jam Nuts

DIN 439 Brass Hex Thin Jam Nuts

BRASS DIN 439 NUTS LOCK NUTS BRASS THIN NUTS JAM NUTS DIN 439 HEX NUTS SELF LOCKING NUTS BRASS HEXAGONAL LOCK NUTS

Diameter d1	M2	M2.5	M3	M4	M5	M6	M8	M10	M12	M14	M16	M20	M24
d2 max.	1	1.2	1.4	2	2.5	3	5	6	8	9	10	14	16
t min.	0.8	1.2	1.2	1.5	2	2	3	4	4.8	5.6	6.4	8	10
e	1.003	1.427	1.73	2.3	2.87	3.44	4.58	5.72	6.86	6.86	9.15	11.43	13.72
s	0.9	1.3	1.5	2	2.5	3	4	5	6	6	8	10	12
Proof Torque min. (NM)	—	—	0.9	2.5	5.0	8.5	20	40	65	65	160	310	—

Material: Brass CZ 121 CW614N CDA 360 Stainless Steel 304 316 for all brass DIN 439 Jam nuts lock nuts self locking hex nuts. hexagonal nuts. These Brass Din 439 nuts are CNC machined from hexagonal bars made at our own factory.

Threads: ISO metric nuts, hexagonal nuts ,UNEF Nuts, UNF nuts UNC nuts BSW nuts

ADDEESS:

Conex Brass Screws Fasteners

Plot 10 B GIDC IND Estate Jamnagar 361004 INDIA

CONTACTS:

PHONE : 91-22-43449300 / 43449327

FAX : 91-22-22834046 / 40023682

EMAIL : sales@conexscrews.com

[CONTACT US](#) | [BACK TO HOME PAGE](#)

KEYWORDS: